

ZT X

LEARN MORE AT [GRAVELY.COM](https://www.gravelly.com)

You'll Never Second Guess Your Gravelly

The ZT X combines zero-turn efficiency with legendary Gravelly performance. Easy-to-handle and comfortable to ride, you'll mow with pro level precision and control with the ZT X. Self-adjusting belts ensure constant tension and the intuitive deck systems deliver fuel efficiency that lets you mow for hours. A fully welded tubular frame gives your ZT X a wicked backbone while the plush, high-back seat provides all-day comfort.



FULLY WELDED TUBULAR FRAME unlike the competitive c-channel frames, this fully-welded, steel tubular frame provides superior rigidity and strength.

CUT SELECTION we cut out the pins and levers to offer a simple and intuitive cutting selection solution. Press the pedal to raise the deck and turn the dial.

11-GAUGE FABRICATED DECK our 4 1/2-inch- deep fabricated deck features an optimized airflow design to produce best-in-class cut quality and discharge performance.

DECK LIFT the deck lift features a 4-point hanging system for deck stability and even cutting performance.

SEATING COMFORT A plush, high-back seat with armrests ensures upgraded comfort for longer mowing sessions.



See your professional Gravelly® dealer for complete warranty details.



42		52		52		60			
MODEL NUMBER		915255		915256		915257		915276	
ENGINE		KOHLER® 7000 PRO TWIN		KOHLER® 7000 PRO TWIN		KAWASAKI® FR691		KAWASAKI® FR691	
HORSEPOWER		22 HP		24 HP		23 HP		23 HP	
DISPLACEMENT		725 CC		725 CC		726 CC		726 CC	
DRIVE SYSTEM		HYDRO-GEAR® EZT TRANSAXLES							
FUEL CAPACITY		2.8 GAL.							
GROUND SPEED		7 MPH / 3 MPH							
(Approx. Mph) (Forward/Reverse)									
DECK									
DECK MATERIAL		11 GA.							
DECK CONSTRUCTION		FABRICATED							
NUMBER OF SPINDLES		3							
BLADE TIP SPEED (FPM)		17,000							
SPINDLE MATERIAL		STEEL MACHINED							
DECK ENGAGEMENT		ELECTRIC WARNER®							
DECK LIFT SYSTEM		FOOT OPERATED							
CUTTING WIDTH		42 IN.		52 IN.		52 IN.		60 IN.	
CUTTING HEIGHT		1.5 IN. - 4.5 IN.							
CUTTING POSITIONS		13							
WHEELS									
FRONT		11 X 6-5							
REAR		20 X 8-8		20 X 10-8					
FEATURES									
SEAT		PLUSH HIGH BACK 18 IN. W/ SEAT SPRINGS & ARM RESTS		PLUSH HIGH BACK 18 IN. W/ SEAT SPRINGS & ARM RESTS		PLUSH HIGH BACK 18 IN. W/ SEAT SPRINGS & ARM RESTS		PLUSH HIGH BACK 18 IN. W/ SEAT SPRINGS, LEVER ADJUST, ARM RESTS	
HOUR METER		STANDARD							
MACHINE									
WEIGHT		570 LBS.		615 LBS.		605 LBS.		634 LBS.	
LENGTH		77.5 IN.							
WIDTH w/ chute		54.2 IN.		63.4 IN.		63.4 IN.		73 IN.	
HEIGHT		40.9 IN.							
WARRANTY									
UNIT		3 YEARS OR 300 HOURS							
ATTACHMENTS & ACCESSORIES									
		2-BAG POWERED BAGGER, MULCH KIT, L.E.D. LIGHT KIT, FLEX-TEND® SHOULDER SUPPORT SYSTEM, CHROME REAR WHEEL COVERS, 48-IN. PLUG AERATOR, 36-IN. POLY ROLLER, 48-IN. DETHATCHER, 15-GALLON SPRAYER, TOW-BEHIND SPREADER, TRAILER HITCH KIT							

GRAVELY.COM

AN ARIENS|CO BRAND

© Copyright 2019 AriensCo. All rights reserved. Registered trademark and ™ trademark of Ariens Company. Briggs & Stratton®, Kohler®, Kawasaki®, Subaru®, Yamaha® and Hydro-Gear® are registered trademarks of their respective companies. The engine horsepower information is provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower will be less. Visit gravelly.com for a complete listing of engine manufacturer power rating information. Product features and specifications subject to change without notice. Photos are a representation of the product; actual product may vary.

