

PRO-STANCE®

LEARN MORE AT [GRAVELY.COM](https://www.gravelly.com)

Smaller Footprint. Bigger Profit.

Compact and easy to trailer, the all-new Pro-Stance is sleeker, more powerful and unbelievably maneuverable.



ADJUSTABLE CRUISE BAR allows the operator to limit and expand the unit's maximum speed in tight working environments.

LOWERED CENTER OF GRAVITY reshaped geometry and redistributed weight provides increased hillside stability and confidence in your ride.

KAWASAKI EFI OFFERING a proven Kawasaki engine with its new EFI option combines reliability and efficiency.

32-INCH DECK the advantage of a stand-on mower enters smaller yards with a 32-inch deck.

ADDED EFFICIENCY reduced complexity gives users freedom to make critical adjustments in just minutes.

HEIGHT-OF-CUT SYSTEM less deck-lifting force, a thumb release and vertical pin system add ease to cutting height adjustments.



NO HOUR LIMIT FIRST TWO YEARS

LIMITED LIFETIME DECK SHELL & FRAME

See your professional Gravelly® dealer for complete warranty details.



	32FL	36FL	48FL	52FL	52FL	60FL	60FL
MODEL NUMBER	994157	994149	994150	994151	994152	994153	994154
ENGINE	KAWASAKI® FS 600 V-TWIN	KAWASAKI® FS 600 V-TWIN	KAWASAKI® FS 730 V-TWIN	KAWASAKI® FS 730 V-TWIN	KAWASAKI® FS 730 V-TWIN EFI	KAWASAKI® FS 730 V-TWIN	KAWASAKI® FS 730 V-TWIN
HORSEPOWER	18.5 HP	18.5 HP	23.5 HP	23.5 HP	25.5 HP	23.5 HP	25.5 HP
DISPLACEMENT	603 CC	603 CC	726 CC	726 CC	726 CC	726 CC	726 CC
DRIVE SYSTEM	HYDRO-GEAR® ZT-3100 TRANSAXLE		HYDRO-GEAR® ZT-3400 TRANSAXLE				
FUEL CAPACITY	6 GAL.		9 GAL.				
GROUND SPEED (Approx. Mph) (Forward/Reverse)	8 MPH / 3 MPH		9 MPH / 4 MPH				
STARTER	ELECTRIC						
DECK							
DECK MATERIAL	7 GA.						
DECK CONSTRUCTION	WELDED						
NUMBER OF SPINDLES	2		3				
BLADE TIP SPEED (FPM)	18,220	18,220	16,900	18,500	18,500	18,500	18,500
SPINDLE HOUSING	FORGED ALUMINUM						
SPINDLE SHAFT	STEEL						
SPINDLE BEARINGS	BALL BEARING						
DECK ENGAGEMENT	ELECTRIC CLUTCH						
DECK LIFT SYSTEM	MANUAL						
CUTTING WIDTH	32 IN.	36 IN.	48 IN.	52 IN.	52 IN.	60 IN.	60 IN.
CUTTING HEIGHTS	1.5 IN. - 5.0 IN.						
CUTTING POSITIONS	15						
WHEELS							
FRONT	11 X 4.00-5 SEMI-PNEUMATIC		13 X 6.50-6 SEMI-PNEUMATIC				
REAR	18 X 6.50 - 8	18 X 8.50 - 8	20X10.50-8 RADIAL				
MACHINE							
WEIGHT	760 LBS.	784 LBS.	875 LBS.	910 LBS.	910 LBS.	940 LBS.	940 LBS.
LENGTH	60.3 IN.		62.5 IN.				
WIDTH (W/O CHUTE)	32.5 IN.	36.5 IN.	50 IN.	55.5 IN.	55.5 IN.	63 IN.	63 IN.
WIDTH (W/ CHUTE)	49 IN.		62.25	67.75	67.75	75.25 IN.	75.25 IN.
HEIGHT	48 IN.		50.5 IN.				
WARRANTY							
UNIT	5 YEAR / 1000 HOUR COMMERCIAL / NO HOUR LIMIT FIRST 2 YEARS						
DECK SHELL & FRAME	LIMITED LIFETIME						
ATTACHMENTS & ACCESSORIES							
MULCHING KIT, OPERATOR CONTROLLED DISCHARGE BAFFLE, GRASS COLLECTOR SYSTEM, HEADLIGHT KIT, TRIMMER HOLDER, BUCKET HOLDER, BACKPACK BLOWER HOLDER							

GRAVELY.COM

AN ARIENS|CO BRAND

© Copyright 2019 AriensCo. All rights reserved. Registered trademark and ™ trademark of Ariens Company. Briggs & Stratton®, Kohler®, Kawasaki®, Subaru®, Yamaha® and Hydro-Gear® are registered trademarks of their respective companies. The engine horsepower information is provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower will be less. Visit gravelly.com for a complete listing of engine manufacturer power rating information. Product features and specifications subject to change without notice. Photos are a representation of the product; actual product may vary.

