

PRO-TURN[®]

Z

LEARN MORE AT [GRAVELLY.COM](https://www.gravelly.com)

Performance From Beginning To End.

The Gravelly Pro-Turn Z series packs commercial grade features into every inch of this durable workhorse. The Pro-Turn Z ships standard with ROPS, seat isolators, and a full commercial warranty. Plus, it inherits the unparalleled durability of the Gravelly line, maximizing runtime and performance.



SEATING SYSTEM the high-back seat features arm rests, seat isolators and large-diameter steering arms to reduce fatigue and provide all-day comfort.

DECK LIFT SYSTEM effortless foot-operated system offers 15 cutting positions in .25-inch increments.

DISCHARGE CHUTE The flip-up side discharge chute is designed to avoid potential damage to the surrounding environment.

CBT SYSTEM our exclusive Constant Belt Tension System (CBT) ensures that belt tension is constant, keeping the blade tip speed and cutting results consistent.

FOLDABLE ROPS comes standard to provide extra protection for the operator.

CANISTER FILTRATION commercial canister filtration system protects your investment for a long road ahead.



See your professional Gravelly[®] dealer for complete warranty details.



48		52		60			
MODEL NUMBER		991192		991194		991196	
ENGINE				GRAVELY			
FILTRATION				HEAVY-DUTY AIR CLEANER			
HORSEPOWER				26.5 HP			
DISPLACEMENT				764 CC			
FILTRATION							
DRIVE SYSTEM				HYDRO-GEAR® ZT-3100 TRANSAXLES			
FUEL CAPACITY				5.0 GAL.			
GROUND SPEED (Approx. Mph) (Forward/Reverse)				8 MPH / 4 MPH			
DECK							
DECK MATERIAL		10 GA. STEEL W/ 10 GA. SPINDLE REINFORCEMENT					
DECK CONSTRUCTION		FABRICATED					
NUMBER OF SPINDLES		3					
BLADE TIP SPEED (FPM)		18,000					
SPINDLE HOUSING MATERIAL		FORGED ALUMINUM					
SPINDLE BEARINGS		BALL BEARING					
DECK ENGAGEMENT		ELECTRIC OGURA®					
CUTTING WIDTH		48 IN.		52 IN.		60 IN.	
CUTTING HEIGHTS		1.0 IN. - 5.0 IN.					
CUTTING POSITIONS		15					
WHEELS							
FRONT AXLE		FIXED					
FRONT		SMOOTH 13 X 6.50-6					
REAR		TURF 22 X 10-12		TURF 22 X 10.5-12		TURF 22 X 12-12	
FEATURES							
SAFETY		ANSI CERTIFIED					
SEAT		20 IN. HIGH BACK COMFORT W/ INTEGRATED ISOLATION					
MACHINE							
WEIGHT		923 LBS.		932 LBS.		953 LBS.	
LENGTH		81 IN.					
WIDTH (W/ CHUTE UP/DOWN)		51 IN. / 63 IN.		55 IN. / 67 IN.		63 IN. / 75 IN.	
HEIGHT (W/ ROPS EXT/DOWN)		72 IN. / 49 IN.					
WARRANTY							
UNIT		4 YEAR / 750 HOUR LIMITED					
ATTACHMENTS & ACCESSORIES							
MULCHING KIT, DISCHARGE COVER KIT, TRAILER HITCH KIT, HEADLIGHT KIT, STRIPING KIT, SUN SHADE KIT, POWERED BAGGER KIT, OPERATOR CONTROLLED DISCHARGE CHUTE							

GRAVELY.COM

AN ARIENS|CO BRAND

© Copyright 2019 AriensCo. All rights reserved. Registered trademark and ™ trademark of Ariens Company. Briggs & Stratton®, Kohler®, Kawasaki®, Subaru®, Yamaha® and Hydro-Gear® are registered trademarks of their respective companies. The engine horsepower information is provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower will be less. Visit gravelly.com for a complete listing of engine manufacturer power rating information. Product features and specifications subject to change without notice. Photos are a representation of the product; actual product may vary.

